

8" BLOCK & BRICK FOUNDATION

13'-0"

FTG. FOR STEPS FIELD LOCATE

PORCH FLOOR :
4" CONCRETE SLAB /w
FIBRE MESH REINFORCEMENT
COMPACTED GRANULAR FILL

24" WIDE X 10" THICK
CONT. CONCRETE FTG.
W/ 2 #4 BARS

SLAB EDGE SUPPORT
8" BLOCK PIERS

2'-6" 5'-4" 2'-6"

8" BLOCK

NOTE: BLOCK SOLID FROM
FOUNDATION TO SUPPORT
MEMBERS @ ALL BEARING PTS.

24" WIDE X 10" THICK
CONT. CONCRETE FTG.
W/ 2 #4 BARS

2x10 FLOOR JOISTS
@ 16" o.c.

3-2x10 P.T.
Built-Up Beam

8" X 16"
CONCRETE
BLOCK PIERS

6Mil Poly
GROUND COVER

NOTE: DOUBLE JOIST
UNDER ALL PARTITIONS
PARALLEL TO JOIST

16" X 16"
CONCRETE
BLOCK PIER
@ FOUNDATION
HEIGHT

3-2x10 P.T.
Built-Up Beam

8" X 16"
CONCRETE
BLOCK PIERS

8" X 16"
CONCRETE
BLOCK PIER
@ FOUNDATION
HEIGHT

2x10 FLOOR JOISTS
@ 16" o.c.

FOUND.
HGT.

FOUND.
HGT.

TRIPLE
JOIST

4" BLOCK & BRICK
FOUNDATION

14'-0"

4'-9"

2'-4"

5'-0"

2'-4"

2'-0"

5'-3"

2'-4"

8'-0"

7'-11"

3"

5'-6"

6'-9"

5'-6"

45'-6"

31'-0"

4'-10"

4'-10"

4'-10"

4'-10"

4'-10"

4'-10"

4'-10"

4'-10"

4'-10"

4'-10"

4'-10"

4'-10"

4'-10"

4'-10"

4'-10"

4'-10"